


Unité FZ ultra-compacte • R32

Unité murale FZ ultra-compacte Inverter

L'unité FZ a été repensée dans le but de simplifier l'installation et la maintenance. Elles nécessitent moins d'étapes et moins de temps.



Unité FZ ultra-compacte • R32		Monophasé			
		2.5 kW	3.4 kW	5 kW	6 kW
Cooling capacity (Nominal)	kW	2,50 (0,85 - 3,00)	3,40 (0,85 - 3,90)	5,00 (0,98 - 5,40)	6,00 (0,98 - 6,50)
EER (Nominal) (1)	W/W	3,68 (4,05 - 3,33)	3,18 (3,54 - 3,05)	3,03 (3,92 - 2,90)	3,03 (3,92 - 2,83)
SEER (2)		6,20 A++	6,10 A++	6,50 A++	6,30 A++
Heating capacity (Nominal)	kW	3,15 (0,80 - 3,60)	3,84 (0,80 - 4,40)	5,40 (0,98 - 7,50)	6,80 (0,98 - 8,00)
Heating capacity at -7°C	kW	2,14	2,60	4,58	5,10
COP (Nominal) (1)	W/W	4,04 (4,21 - 3,46)	3,66 (4,10 - 3,41)	3,42 (4,67 - 3,06)	3,15 (4,26 - 3,02)
SCOP (2)		4,20 A+	4,20 A+	4,10 A+	4,00 A+
Refrigerant (R32) / CO2 Eq.	kg / T	0,54 / 0,365	0,67 / 0,452	1,14 / 0,770	1,11 / 0,749
Operating range (Cool - Min)	°C	-10 ~ +43	-10 ~ +43	-10 ~ +43	-10 ~ +43

Accessoires

